

PAT-NO: JP02002127717A
DOCUMENT-IDENTIFIER: JP 2002127717 A
TITLE: PNEUMATIC TIRE
PUBN-DATE: May 8, 2002

INVENTOR-INFORMATION:

NAME	COUNTRY
OYAMA, TOSHIRO	N/A

ASSIGNEE-INFORMATION:

NAME	COUNTRY
YOKOHAMA RUBBER CO LTD:THE	N/A

APPL-NO: JP2000328750

APPL-DATE: October 27, 2000

INT-CL (IPC): B60C013/00

ABSTRACT:

PROBLEM TO BE SOLVED: To provide a pneumatic tire which is capable of retaining its carcass line nearly uniformly on the circumference of the tire without impairing the visibility of marks such as letters, figures, signs and diagrams.

SOLUTION: In a pneumatic tire provided with a pair of right and left bead parts 3, a carcass layer 4 laid between the bead parts 3 and projecting marks 9 on the surface 2a of sidewall parts 2, recessed parts 10 are provided adjacent to the projecting marks 9 on the surface 2a of the sidewall parts 2, and the volume v of the recessed parts 10 to the volume V of the

projecting marks 9 is
set in the range of 0.8V≤v≤1.2V.

COPYRIGHT: (C) 2002, JPO